

# MATERIAL SAFTY DATA SHEET

Issued: MARCH 12, 2015

# $\mu$ S C

1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY

Product name:

μSC

Product type:

Additive for dielectric oil

Supplier:

MAKINO MILLING MACHINE CO.,LTD.

Address:

3-19, Nakane2-chome, Meguro-ku, Tokyo152, Japan

Telephone Number:

+81-3-3724-7701

Fax Number:

+81-3-3724-2815

Emergency telephone number

+81-3-46-286-6736

2. HAZARDS IDENTIFICATION

**GHS Classification:** 

Classification criteria do not apply.

Other hazards not included:

No information.

in the GHS classification

Main symptoms:

No information.

Emergency overview:

No information.

3. COMPSITION/INFORMATION ON INGREDIENTS

Single substance or mixture:

Mixture

Common chemical name (generic name):

Synthetic hydrocarbons and Carbon

Preparation description:

Synthetic hydrocarbons > 60%, Carbon > 30% official: Not relevant.

Publication number in Japanese official: gazette (Law Concerning the Examination

and Regulation of the Manufacture, etc. of

Chemical Substances; Chemical

Substance Control Law)

Publication number in Japanese official:

Not relevant.

gazette(Industrial Safety and Health Act)

4. FIRST AID MEASURES

Symptoms and effects:

Not expected to give rise to an acute hazards under normal

condition of use.

First Aid - Inhalation:

In the unlikely event of dizziness or nausea, remove casualty to fresh

air. If symptoms persist, obtain medical attention.

First Aid - Skin:

Remove contaminated clothing and wash affected skin with soap and

water. If persistent irritation occurs, obtain medical attention

immediately.

First Aid - Eye:

Flush eye with copious quantities of water. If persistent irritation

occurs, obtain medical attention.

First Aid - ingestion:

Wash out mouth with water and obtain medical attention. DO NOT

INDUCE VOMITING.

Advice to physicians:

Treat symptomatically. Aspiration into the lungs may result in

chemical pneumonitis.

5. FIRE FIGHTING MEASURES

Specific hazards: Combustion is likely to give rise to a complex mixture of airborne solid

and liquid particulates and gases, including carbon monoxide, oxides

of sculpture, and unidentified organic and inorganic compounds. Foam and dry chemical powder. Carbon dioxide, sand or earth may

Extinguishing media: be used for small fires only.

Unsuitable extinguishing media: Water in a jet. Use of Halon extinguishers should be avoided for

environmental reasons.

Proper protective equipment including breathing apparatus must be **Protective equipment:** 

worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Avoid contact with: skin and eyes. wear impermeable gloves and boots.

Personal protection: Environmental precautions:

Prevent from spreading or entering into drains, ditches rivers by using

sand, earth, or other appropriate barriers. Inform local authorities if this cannot be prevented.

Clean-up methods-small spillage: Absorb liquid with sand or earth. Sweep up and remove to a

suitable, clearly marked container for disposal in accordance with

local regulations.

Clean-up methods-large spillage: Prevent from spreading by making a barrier with sand, earth or

other containment material. Reclaim liquid directly or in an absorbent.

Dispose of as for small spills.

7. HANDLING AND STORAGE

Handling:

When handling product in drums, safety footwear should be worn and

proper handling equipment should be used. Prevent spillages.

Storage:

Keep in a cool, dry, well-ventilated place. Use properly labeled and closed containers. Avoid direct sunlight, heat sources, and strong

oxidizing agents.

Storage temperature:

Recommended materials:

0°C minimum to 50°C maximum.

Unsuitable materials:

Other information:

For container linings, use: mild steel or high density polyethylene.

For containers or container linings, avoid: PVC.

Polyethylene containers should not be exposed to high temperatures

because of possible risk of distortion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering control measures: Use local exhaust ventilation if there is a risk of inhalation of vapours,

mists or aerosols.

Occupational exposure standards: Threshold limit values are given below. Lower exposure limits

5

10

may apply locally:

Component name Oil mist, mineral

Limit type Value 8-hour TWA

Unit mg/m<sup>3</sup> Other information **ACGIH** 

Hygiene measures:

15-mini STEL

mg/m<sup>3</sup>

**ACGIH** 

Respiratory protection:

Wash hands before eating, drinking, smoking and using the toilet. Not normally required. If oil mist cannot be controlled, a respirator

fitted with an organic vapor cartridge combined with a particulate

pre-filter should be used. Hand protection:

Eye protection: **Body protection:**  PVC or nitric rubber gloves. Wear safety glasses or fill face shield if splashes are likely to occur.

Minimize all forms of skin contact. Wear overralls to minimize contamination of personal clothing. Launder overalls

undergarments regularly.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Compound of individual and liquid at ambient temperature.

Color:

Black

Odor:

No odor >210°C

**Initial boiling point:** 

Density:

0.85

Vapor density (air=1):

>1 at 20°C

Flash point: Flammability limit - lower: 86°C

Flammability limit - upper:

1% v/v (typical) 7% v/v (typical) >200°C (typical)

Auto-ignition temperature: Solubility in water:

Negligible

#### 10. STABILITY/REACTIVITY

Stability:

stable

Condition to avoid:

Extremes of temperature and direct sunlight.

Material to avoid:

Strong oxidizing agents

Hazardous decomposition product: Hazardous decomposition products are not expected to form

during normal storage.

#### 11. TOXICOLOGICAL UNFORMATION

Basis for assessment:

Toxicological data have not been determined specifically for this

product. Information given is based on a knowledge of the

components and the toxicology of similar products.

Acute toxicity - oral:

Believed to be greater than 5g/kg (rat)

Practically non-toxic

Acute toxicity - dermal:

Believed to be greater than 3g/kg (rabbit)

Practically non-toxic

Acute toxicity - inhalation:

Data not available.

Eye irritation: Skin irritation: Expected to be slightly irritant. Expected to be slightly irritant.

Respiratory irritation:

If mists are inhaled, slightly irritation of respiratory tract may occur.

Skin sensitization:

Not expected to be a skin sensitizer.

Carcinogenicity:

Product is based on the types of shown to be non-carcinogenic in

animal skin-painting studies.

Mutagenic:

Not considered to be a mutagenic hazard.

Other information:

Without the information for which the information for reacting to water

and generating harmful gas is useful up to now.

Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. All used oil should be handled with caution and skin contract avoided

as far as possible.

#### 12. ECOLAGICAL INFORMATION

**Basis for assessment:** 

Eco toxicological data have not been determined specifically for this product. Information given is based on knowledge of the components

and eco toxicology of similar products.

Mobility:

Liquid under most environmental conditions. Floats on water. If it

enters soil, it will absorb to soil particles and will not be mobile.

Persistence/degradability:

Not readily biodegradable. Major constituents are expected to be inherently bio degradable, but the product contains components that

may persist in the environment.

Bioaccumulation:

Has the potential to bioaccumulation.

**Eco toxicity:** 

Poorly soluble mixture. Product is expected to be practically non-toxic

to aquatic organisms.

(LC/EC50expressed as the nominal amount of product required to

prepare aqueous test extract)

#### 13. DISPOSAL CONSIDERATIONS

Waste disposal:

Recycle or dispose of in accordance with prevailing regulation, preferably to a recognized collector or contractor. The competence of the contractor to deal satisfactorily with this type of product should be

established beforehand.

Container disposal:

200 litter drums should be emptied and returned to the supplier or sent to a drum reconditioned without removing or defacing markings

or labels.

Non-reusable small metal and plastic containers should be recycled

where possible, or disposed of as domestic refuse.

## 14. TRANSPORT INFOMATION

International regulations

UN classification:

Not applicable

UN number:

None allocated

Not dangerous for conveyance under UN, IMO, ADR/RID and IATA/ICAO codes. Make sure the containers are free of damage of leaks. Load carefully to protect from impact, overturning, falls or breaking. Implement special measures to prevent load shifting.

#### 15. REGULATORY INFORMATION

**EC Classification:** 

Not classified as Dangerous under EC criteria

**EINECS/ELINCS (EC):** 

All components listed or polymer exempt.

TSCA (USA):

All components listed.

MITI (JAPAN):

All components listed.

#### 16. OTHER INFORMATION

References

1) ANSI Z 129.1-1994 American National Standards Institute..

2) Thresholds limit values for chemicals substances and physical agents and biological exposure indices, ACGIH (2012)

3) SDS of EU suppliers (2012-2014)

SDS Author

Company and Section name: MAKINO MILLING MACHINE CO.,LTD.

EDM R&D DIVISION

TEL

+81-46-286-6736

FAX

+81-46-286-6966

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not be construed as guaranteeing any specific property of the product.